

Element/Attribute	Description
<code>&lt;acronym&gt; &lt;/acronym&gt;</code>	Marks acronym text (deprecated)
<code>&lt;address&gt; &lt;/address&gt;</code>	Marks address text
<code>&lt;applet&gt; &lt;/applet&gt;</code>	Embeds an applet into the browser (deprecated)
<code>align="align"</code>	Specifies the alignment of the applet with the surrounding text where <i>align</i> is <i>absmiddle</i> , <i>absbottom</i> , <i>baseline</i> , <i>bottom</i> , <i>center</i> , <i>left</i> , <i>middle</i> , <i>right</i> , <i>texttop</i> , or <i>top</i> .
<code>alt="text"</code>	Specifies alternate text for the applet (deprecated)
<code>archive="url"</code>	Specifies the URL of an archive containing classes and other resources to be used with the applet (deprecated)
<code>code="url"</code>	Specifies the URL of the applet's code/class (deprecated)
<code>codebase="url"</code>	Specifies the URL of all class files for the applet (deprecated)
<code>datafld="text"</code>	Specifies the data source that supplies bound data for use with
<code>datasrc="text"</code>	Specifies the ID or URL of the applet's data source
<code>height="integer"</code>	Specifies the height of the applet in pixels
<code>hspace="integer"</code>	Specifies the horizontal space around the applet in pixels (deprecated)
<code>mayscript="mayscript"</code>	Permits access to the applet by programs embedded in the document
<code>name="text"</code>	Specifies the name assigned to the applet (deprecated)
<code>object="text"</code>	Specifies the name of the resource that contains a serialized representation of the applet (deprecated)
<code>src="url"</code>	Specifies an external URL reference to the applet
<code>vspace="integer"</code>	Specifies the vertical space around the applet in pixels (deprecated)
<code>width="integer"</code>	Specifies the width of the applet in pixels (deprecated)
<code>&lt;area /&gt;</code>	Marks an image map hotspot
<code>alt="text"</code>	Specifies alternate text for the hotspot
<code>coords="value list"</code>	Specifies the coordinates of the hotspot; the value list depends on the shape of the hotspot: <i>shape="rect"</i> " <i>left, right, top, bottom</i> " <i>shape="circle"</i> " <i>x_center, y_center, radius</i> " <i>shape="poly"</i> " <i>x1, y1, x2, y2, x3, y3, ...</i> "
<code>href="url"</code>	Specifies the URL of the document to which the hotspot points
<code>hreflang="lang"</code>	Language of the hyperlink destination
<code>media="media"</code>	The media for which the destination of the hyperlink was designed
<code>rel="text"</code>	Specifies the relationship between the current page and the destination of the link
<code>nohref="nohref"</code>	Specifies that the hotspot does not point to a link
<code>shape="rect circle polygon"</code>	Specifies the shape of the hotspot
<code>target="text"</code>	Specifies the target window or frame for the link
<code>&lt;article&gt; &lt;/article&gt;</code>	Structural element marking a page article (HTML5)
<code>&lt;aside&gt; &lt;/aside&gt;</code>	Structural element marking a sidebar that is tangentially related to the main page content (HTML5)
<code>&lt;audio&gt; &lt;/audio&gt;</code>	Marks embedded audio content (HTML5)
<code>autoplay="autoplay"</code>	Automatically begins playback of the audio stream
<code>preload="none metadata auto"</code>	Specifies whether to preload data to the browser
<code>controls="controls"</code>	Specifies whether to display audio controls